

This safety data sheet complies with the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Issuing Date 26-Sep-2021**Revision Date** 26-Sep-2021**Revision Number** 2.03**Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product identifier**

Product Code(s)	SDS-06198 EN E
Product Name	Support, SUP705 B™
PN (Part Number)	OBJ-03050, OBJ-04045, OBJ-06285, OBJ-02271, OBJ-18024
Denmark PR No	N/A
Chemical name	Acrylic formulation
Pure substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Printing inks
Uses advised against	This product is a cartridge containing ink. Under normal conditions of use, the substance is released from a cartridge only inside an appropriate printing system, and therefore, exposure is limited

1.3. Details of the supplier of the safety data sheet**Importer**

Stratasys EMEA Regional Office
Airport Boulevard B 120
77836 Rheinmünster, Germany
Phone: +49-7229-7772-0

For further information, please contact

E-mail address info@Stratasys.com

1.4. Emergency telephone number

Emergency Telephone +44 1235 239670 - Europe - Multi lingual response

Austria	Poison Information Centre (AT): +43-(0)1-406 43 43
Belgium	Poison Centre (BE): +32 70 245 245
Bulgaria	Poison Center (BG): +359 (0)2 9154 233
Croatia	Poison Control (CR): +385 1 2348 342
Czech Republic	Poison Control (CS): +420 224 919 293, +420 224 915 402
Denmark	Poison Control Hotline (DK): +45 82 12 12 12
Estonia	Poison Control (ET): 112, 16662, +372 7943 794
Finland	Poison Information Centre (FI): +358 9 471 977
France	ORFILA (FR): + 01 45 42 59 59
Greece	Poison Information Center (EL): +30 210 779 3777 Emergency Poison Centre telephone number, Aglaia Kyriakou Children's Hospital
Hungary	Poison Information Service (HU): +36 (06) 80 201-199

Ireland	+353 (0)1 809 2166 – public poisons information line
Italy	Poison Centre, Milan (IT): +39 02 6610 1029
Latvia	State Fire and Rescue Service, phone number: 112. State Toxicology Center, Poisoning and Drug Information Center, Hipokrāta 2, Riga, Latvia, LV-1079, phone number +371 67042473
Lithuania	Poison Information Office (LT): 112, +370 (8)5 236 20 52, +370 (8)6 875 33 78
Netherlands	National Poisons Information Center (NVIC): 030-274 8888 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway	Poisons Information (NO): + 47 22 591300
Portugal	Poison Information Centre (PT): +351 808 250 250
Slovakia	Poison Information Service (SK): +421 911 166066
Spain	Poison Information Service (ES): +34 91 562 04 20
Sweden	112 – ask for Poisons Information
Switzerland	Tox Info Suisse: 145, +41 44 251 51 51

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Dermal	Category 4 - (H312)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1A - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains Acrylic acid, 2-hydroxyethyl ester, Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide



Signal word

Danger

Hazard statements

H312 - Harmful in contact with skin
 H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H318 - Causes serious eye damage
 H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand
 P102 - Keep out of reach of children
 P273 - Avoid release to the environment
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a POISON CENTER or doctor
 P391 - Collect spillage
 P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Toxic to aquatic life.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances**3.2 Mixtures**

Chemical name	EC No	CAS No	Index no.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Polyethylene Glycol 400	-	25322-68-3	-	10 - 30	Not classified	No data available
Propane-1,2-diol	200-338-0	57-55-6	-	10 - 30	Not classified	01-2119456809-23-0006
1,2,3-propanetriol	200-289-5	56-81-5	-	10 - 30	Not classified	No data available
Acrylic acid, 2-hydroxyethyl ester	212-454-9	818-61-1	607-072-00-8	3-10	Acute Tox. 4 (H302) Acute Tox. 2 (H310) Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) STOT SE 3 (H335) Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412)	No data available
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	-	55818-57-0	-	0.3-1	Skin Sens. 1 (H317)	01-2119490020-53-XXX X
Ethoxylated Trimethylolpropane Triacrylate	-	28961-43-5	-	0.3-1	Skin Sens. 1B (H317) Eye Irrit. 2 (H319)	No data available
Proprietary	No information available	-	-	0.1 - 0.3	Skin Sens. 1A (H317) Aquatic Chronic 4 (H413)	No data available
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	204-881-4	128-37-0	-	0.1 - 0.3	Acute Tox. 4 H302 Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	No data available
Tris (N-hydroxy-N-nitrosophenylamino-O,O') aluminium	239-341-7	15305-07-4	-	0.1 - 0.3	Acute Tox. 4 (H302) Skin Sens. 1B (H317) Aquatic Chronic 1 (H410)	No data available
4-Methoxyphenol/ Mequinol	205-769-8	150-76-5	-	<0.1	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Repr. 2 (H361d) Aquatic Chronic 3 (H412)	No data available
Heptane	205-563-8	142-82-5	-	<0.1	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) Flam. Liq. 2 (H225)	No data available

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Get immediate medical advice/attention. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. If symptoms persist, call a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

Section 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing agent suitable for type of surrounding fire
Class B fires: Use carbon dioxide (CO₂), regular dry chemical (sodium bicarbonate), regular foam (Aqueous Film Forming Foam-AFFF), or water spray to cool containers

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Move containers from fire area if you can do it without risk. Cool containers with flooding quantities of water until well after fire is out. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Keep out of drains, sewers, ditches and waterways. Inhalation is a health risk. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Occupational Spill Release Intact cartridges do not pose a leak or spill hazard. Damaged cartridges may leak uncured ink. Stop leak if you can do it without risk Use water spray to reduce vapours or divert vapour cloud drift Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container Keep out of drains, sewers, ditches and waterways

Other Information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling Avoid breathing vapours or mists. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Do not eat, drink or smoke when using this product.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store in a cool, well ventilated area. Store in accordance with local regulations. Keep container tightly closed. Store between 15 °C and 27 °C. Shipment temperature (up to 5 weeks) is -20 °C to 50 °C. Store in a combustible storage area away from heat and open flame.

Hints on joint storage

Storage class LGK10 - Combustible liquids unless storage class 3

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Material Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure disclaimer Personal protection measures are only needed if cartridge is damaged punctured causing spillage of material.

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom	France	Spain	Germany
Polyethylene Glycol 400 25322-68-3	-	-	-	-	TWA: 200 mg/m ³
Propane-1,2-diol 57-55-6	-	TWA: 150 ppm TWA: 474 mg/m ³ TWA: 10 mg/m ³ STEL: 450 ppm STEL: 1422 mg/m ³ STEL: 30 mg/m ³	-	-	-

1,2,3-propanetriol 56-81-5	-	TWA: 10 mg/m ³ STEL: 30 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 200 mg/m ³
2,6-Bis(1,1-Dimethylethyl))-4-Methyl-Phenol 128-37-0	-	TWA: 10 mg/m ³ STEL: 30 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
4-Methoxyphenol/ Mequinol 150-76-5	-	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³	-
Heptane 142-82-5	TWA 500 ppm TWA 2085 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m ³ STEL: 1500 ppm STEL: 6255 mg/m ³	TWA: 400 ppm TWA: 1668 mg/m ³ TWA: 1000 mg/m ³ STEL: 500 ppm STEL: 2085 mg/m ³ STEL: 1500 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 500 ppm TWA: 2100 mg/m ³
Chemical name	Italy	Portugal	Netherlands	Finland	Denmark
Polyethylene Glycol 400 25322-68-3	-	-	-	-	TWA: 1000 mg/m ³
1,2,3-propanetriol 56-81-5	-	TWA: 10 mg/m ³	-	TWA: 20 mg/m ³	-
Acrylic acid, 2-hydroxyethyl ester 818-61-1	-	-	-	-	TWA: 1 ppm TWA: 5 mg/m ³ H*
2,6-Bis(1,1-Dimethylethyl))-4-Methyl-Phenol 128-37-0	-	TWA: 2 mg/m ³	-	TWA: 10 mg/m ³ STEL: 20 mg/m ³	TWA: 10 mg/m ³
4-Methoxyphenol/ Mequinol 150-76-5	-	TWA: 5 mg/m ³	-	-	TWA: 5 mg/m ³
Heptane 142-82-5	TWA: 500 ppm TWA: 2085 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m ³ STEL: 500 ppm	TWA: 1200 mg/m ³ STEL: 1600 mg/m ³	TWA: 300 ppm TWA: 1200 mg/m ³ STEL: 500 ppm STEL: 2100 mg/m ³	TWA: 200 ppm TWA: 820 mg/m ³
Chemical name	Austria	Switzerland	Poland	Norway	Ireland
Polyethylene Glycol 400 25322-68-3	TWA: 1000 mg/m ³ STEL 4000 mg/m ³	TWA: 500 mg/m ³	-	-	-
Propane-1,2-diol 57-55-6	-	-	TWA: 100 mg/m ³	TWA: 25 ppm TWA: 79 mg/m ³ STEL: 37.5 ppm STEL: 118.5 mg/m ³	TWA: 10 mg/m ³ TWA: 150 ppm TWA: 470 mg/m ³ STEL: 1410 mg/m ³ STEL: 30 mg/m ³ STEL: 450 ppm
1,2,3-propanetriol 56-81-5	-	TWA: 50 mg/m ³ STEL: 100 mg/m ³	TWA: 10 mg/m ³	-	-
2,6-Bis(1,1-Dimethylethyl))-4-Methyl-Phenol 128-37-0	TWA: 10 mg/m ³	TWA: 10 mg/m ³ STEL: 40 mg/m ³	-	-	TWA: 2 mg/m ³ STEL: 6 mg/m ³
4-Methoxyphenol/ Mequinol 150-76-5	TWA: 5 mg/m ³ STEL 10 mg/m ³	-	TWA: 5 mg/m ³	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³ STEL: 15 mg/m ³
Heptane 142-82-5	TWA: 500 ppm TWA: 2000 mg/m ³ STEL 2000 ppm STEL 8000 mg/m ³	TWA: 400 ppm TWA: 1600 mg/m ³ STEL: 400 ppm STEL: 1600 mg/m ³	STEL: 2000 mg/m ³ TWA: 1200 mg/m ³	TWA: 200 ppm TWA: 800 mg/m ³ TWA: 40 ppm TWA: 275 mg/m ³ STEL: 250 ppm STEL: 1000 mg/m ³ STEL: 60 ppm STEL: 343.75 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m ³ STEL: 1500 ppm STEL: 6255 mg/m ³
Chemical name	Sweden	Slovakia			

Chemical name	Sweden	Slovakia			
Polyethylene Glycol 400 25322-68-3	-	TWA: 1000 mg/m ³	-	-	-
1,2,3-propanetriol 56-81-5	-	TWA: 11 mg/m ³	-	-	-
Acrylic acid, 2-hydroxyethyl ester 818-61-1	NGV: 1 ppm NGV: 5 mg/m ³ Sensitizer * Vägledande KGV: 2 ppm Vägledande KGV: 10 mg/m ³		-	-	-
Heptane 142-82-5	NGV: 200 ppm NGV: 800 mg/m ³ NGV: 350 mg/m ³ Vägledande KGV: 300 ppm Vägledande KGV: 1200 mg/m ³	TWA: 500 ppm TWA: 2085 mg/m ³	-	-	-

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand Protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

Environmental exposure controls No information available.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Ink cartridge
Odour Characteristic
Colour clear
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	N/A	
Melting point / freezing point	No data available	None known

Boiling point / boiling range	No data available	None known
Flash point	109 - 109 °C	
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit:	No data available	
Lower flammability limit	No data available	
Vapour pressure	No data available	None known
Vapour density	No data available	None known
Relative density	1.12	g/cm3
Water solubility	Soluble in water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No information available	
Oxidising properties	No information available	

9.2. Other information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity Heating may cause a fire.

10.2. Chemical stability

Stability Decomposes on exposure to light. Unstable if heated.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Uncured ink will polymerize on exposure to light.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to heat and light.

10.5. Incompatible materials

Incompatible materials Not applicable under normal conditions of use and storage.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal Decomposition Products. Combustion: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects**Information on likely routes of exposure****Product Information**

Inhalation	May cause irritation of respiratory tract. (based on components).
Eye contact	Severely irritating to eyes. Causes serious eye damage. May cause burns. May cause irreversible damage to eyes. (based on components).
Skin contact	May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. (based on components).

Information on toxicological effects

Symptoms	Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.
-----------------	---

Numerical measures of toxicity**Acute toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	15,989.70 mg/kg
ATEmix (dermal)	1,459.20 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Polyethylene Glycol 400	= 22 g/kg = 22 g/kg (Rat)	> 20 g/kg (Rabbit)	-
Propane-1,2-diol	= 20 g/kg = 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-
1,2,3-propanetriol	= 12600 mg/kg = 12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 2.75 mg/L (Rat) 4 h
Acrylic acid, 2-hydroxyethyl ester	= 548 mg/kg = 548 mg/kg (Rat)	> 1000 mg/kg (Rat)	-
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	>2000 mg/kg (Rat)	>2000 mg/kg	-
Ethoxylated Trimethylolpropane Triacrylate	-	> 13200 mg/kg (Rabbit)	-
Proprietary	> 2000 mg/kg > 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	> 2930 mg/kg > 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
4-Methoxyphenol/ Mequinol	= 1600 mg/kg = 1600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Heptane	-	= 3000 mg/kg (Rabbit)	> 73.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
----------------------------------	---

Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact. Classification based on data available for ingredients.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity STOT - single exposure	No information available. No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Propane-1,2-diol	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51400: 96 h Pimephales promelas mg/L LC50 static 51600: 96 h Oncorhynchus mykiss mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50	-	1000: 48 h Daphnia magna mg/L EC50 Static
1,2,3-propanetriol	-	51 - 57: 96 h Oncorhynchus mykiss mL/L LC50 static	-	-
Acrylic acid, 2-hydroxyethyl ester	-	4.8: 96 h Pimephales promelas mg/L LC50 flow-through	-	0.78: 48 h Daphnia magna mg/L EC50
Ethoxylated Trimethylolpropane Triacrylate	-	1.95: 96 h Danio rerio mg/L LC50 static	-	-
Proprietary	-	90: 96 h Danio rerio µg/L LC50 semi-static	-	-
2,6-Bis(1,1-Dimethylethyl))-4-Methyl-Phenol	6: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.42: 72 h Desmodesmus subspicatus mg/L EC50	-	-	-
4-Methoxyphenol/ Mequinol	-	28.5: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 84.3: 96 h Pimephales promelas mg/L LC50 flow-through	-	-
Heptane	-	375.0: 96 h Cichlid fish mg/L LC50	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
1,2,3-propanetriol	-1.76
Acrylic acid, 2-hydroxyethyl ester	0.21
2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol	4.17
4-Methoxyphenol/ Mequinol	1.3
Heptane	4.66

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

12.6. Other adverse effects

Other adverse effects No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Waste codes / waste designations according to EWC / AVV 08 03 12* Waste ink containing dangerous substances.

Section 14: TRANSPORT INFORMATION

Additional information The environmentally hazardous substance mark is not required when transported in sizes of ≤5L or ≤5kg
The marine pollutant mark is not required when transported in sizes of ≤5L or ≤5kg

IMDG

14.1 UN number or ID number UN3082
14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class(es) 9
14.4 Packing group III
Description UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol, Tris (N-hydroxy-N-nitrosophenylamino-O,O') aluminium), 9, III, Marine pollutant
14.5 Marine pollutant This product contains a chemical which is listed as a severe marine pollutant according to

IMDG/IMO
 Environmental hazards Yes
 14.6 Special Provisions 274, 335, 969
 EmS-No F-A, S-F
 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

RID

14.1 UN number or ID number UN3082
 14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 14.3 Transport hazard class(es) 9
 Labels 9
 14.4 Packing group III
 Description UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol, Tris (N-hydroxy-N-nitrosophenylaminato-O,O') aluminium), 9, III
 14.5 Environmental hazards Yes
 14.6 Special Provisions 274, 335, 375, 601
 Classification code M6

ADR

14.1 UN number or ID number 3082
 14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 14.3 Transport hazard class(es) 9
 Labels 9
 14.4 Packing group III
 Description 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol, Tris (N-hydroxy-N-nitrosophenylaminato-O,O') aluminium), 9, III
 14.5 Environmental hazards Yes
 14.6 Special Provisions 274, 335, 601, 375
 Classification code M6
 Tunnel restriction code (-)

IATA

14.1 UN number or ID number UN3082
 14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
 14.3 Transport hazard class(es) 9
 14.4 Packing group III
 Description UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,6-Bis(1,1-Dimethylethyl)-4-Methyl-Phenol, Tris (N-hydroxy-N-nitrosophenylaminato-O,O') aluminium), 9, III
 14.5 Environmental hazards Yes
 14.6 Special Provisions A97, A158, A197
 ERG Code 9L



Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number	Title
Propane-1,2-diol 57-55-6	RG 84	-
Acrylic acid, 2-hydroxyethyl ester 818-61-1	RG 65	-
4-Methoxyphenol/ Mequinol 150-76-5	RG 65	-
Heptane 142-82-5	RG 84	-

Germany

Water hazard class (WGK) slightly hazardous to water (WGK 1)

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorisations and/or restrictions on use:

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Acrylic acid, 2-hydroxyethyl ester - 818-61-1	75.	
Proprietary -	75.	
4-Methoxyphenol/ Mequinol - 150-76-5	75.	
Heptane - 142-82-5	75.	

Persistent Organic Pollutants

Not applicable

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

15.2. Chemical safety assessment

Chemical Safety Report No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet**Full text of H-Statements referred to under section 3**

H225 - Highly flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child
 H400 - Very toxic to aquatic life
 H410 - Very toxic to aquatic life with long lasting effects
 H412 - Harmful to aquatic life with long lasting effects
 H413 - May cause long lasting harmful effects to aquatic life

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value * Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapor	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration toxicity	Calculation method
Ozone	Calculation method

Revision Date 26-Sep-2021

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet derives from a third party source. Whilst we believe that the information is correct as at the date of its publication, we do not make any representations or warranties regarding the accuracy or completeness of the information nor the quality or specification of any materials, substances or mixtures referred to herein (collectively, "Materials"). The information is being provided solely as a guideline for the safe handling, use, consumption, processing, storage, transportation, disposal and release of the Materials. The information may not be sufficient for such purposes and the user should not place any reliance on the information provided. The information may not be applicable to Materials that are combined with any materials or in any process other than as expressly stated herein. We shall not be liable for any kind of liability including, without limitation, damages, losses or expenses, arising out of or as a result of any reliance on the information contained in this Safety Data Sheet.

© 2018-2021 Stratasy Ltd. License granted to make unlimited paper/electronic copies for internal use only. This Safety Data Sheet or sections thereof should not be published, reproduced, modified, or distributed to third parties without prior written consent from Stratasy Ltd.

End of Safety Data Sheet