

# SYNFILL G

## References :

**Glass fiber filler : SynFill G - PF0400**

## Definition :

Glass fiber filler for the reinforcement of **Synthene** polyurethane systems.

Compatible with:

- **PR777**
- **PR700**
- **PR500**
- **PR752**
- **PR408**

Good flowability in the mixture of resins. Easy to use for vacuum castings applications. REACH compatible material.

## Physical properties of the component :

	SynFill G
<b>Fiber Type</b>	E-glass
<b>Colour</b>	White /greyish
<b>Aspect</b>	Round shape
<b>Specific density (g/ cm<sup>3</sup>)</b>	2,54
<b>Bulk density (g/l)</b>	450

## For applications in a vacuum casting machine :

Refer to the Synthene TDS:

- PR777+SynFill G
- PR700+SynFill G
- PR500+SynFill G
- PR752+SynFill G
- PR408+SynFill G



**Hygiene and safety instructions for using:**

Wearing appropriate safety clothes and accessories (gloves, glasses and mask) is highly recommended.

Work in a ventilated room.

For more information, please read the Medical and Safety Data Sheet of the material.

**Packaging:**

Synfill G :

- Box of 30 kg
- Pail of 10 kg

**Storage :**

2 years in the original unopened container, stored between 5 and 30 °C and kept away from moisture and UV-radiation.